

CLAIMS

1. (Cancelled)

2. (Cancelled)

3. (Cancelled)

4. (Cancelled)

5. (Cancelled)

6. (Previously Presented) In a kitchen oven having an infrared gas broiler with a venturi tube assembly extending forwardly from a back wall of the oven for supplying fuel gas and drawing ambient air for combustion through a venturi tube opening at the oven back wall, an improvement comprising;

ducting mounted on the oven back wall and extending over the venturi tube opening,
and

a fan mounted on the oven in communication with said ducting for supplying a positive air flow through the ducting to the venturi tube opening;

wherein said ducting includes a downwardly extending duct on the oven back wall and a laterally extending transfer duct having a first end communicating with said downwardly extending duct, said transfer duct having a second end communicating with the venturi tube opening.

7. (Original) The kitchen oven improvement of claim 6, wherein said ducting includes a duct enclosure at least partially surrounding the venturi tube opening and communicating with said second end of said transfer duct for receiving the positive air flow.

8. (Original) The kitchen oven improvement of claim 7, wherein said duct enclosure has closed sides and top with an open bottom.
9. (Original) The kitchen oven improvement of claim 8, wherein said transfer duct has an upwardly facing L-shaped portion on said second end extending into said duct enclosure.
10. (Original) The kitchen oven improvement of claim 6, 7, 8 or 9 wherein said transfer duct has an upwardly facing L-shaped portion on said first end extending into said downwardly extending duct.
11. (Original) The kitchen oven improvement of claim 6, wherein said first end of said transfer duct is mounted on a rear surface of said downwardly extending duct and an opening is provided between said transfer duct and said downwardly extending duct.
12. (Original) The kitchen oven improvement of claim 6 or 11, wherein said second end of said transfer duct is spaced rearwardly from the oven back wall and includes an opening opposite the venturi tube opening for discharging the positive air flow toward the venturi tube opening.
13. (Cancelled)
14. (Cancelled)
15. (Cancelled)
16. (Cancelled)
17. (Cancelled)
18. (Cancelled)
19. (Cancelled)
20. (Cancelled)

21. (Cancelled)

22. (Cancelled)

23. (Currently Amended) The kitchen oven of claim [[20]] 24, wherein an inlet to said ducting is located adjacent said top wall for drawing ambient air over said top wall of the oven.

24. (Currently Amended) ~~The kitchen oven of claim 20 or 23,~~ A kitchen oven comprising, an oven cell having a top wall, a bottom wall, side walls, a back wall and a front door, said oven cell having a heating means near the bottom wall for baking and an infrared gas broiler near the top wall for broiling, said infrared gas broiler having a venturi tube assembly extending forwardly from said back wall of the oven for supplying fuel gas and drawing ambient air for combustion through a venturi tube opening at said oven back wall, ducting on said oven back wall and extending over said venturi tube opening, and a fan mounted on the oven in communication with said venturi tube opening for supplying a positive flow of air to said venturi tube opening, said ducting having a free flow opening adjacent said venturi tube opening for allowing a free flow of ambient air into said venturi tube opening separate from said positive air flow supply and allowing a discharge of excess air of said positive air flow supply, wherein said ducting includes a downwardly extending duct on the oven back wall and a laterally extending transfer duct having a first end communicating with said downwardly extending duct, said transfer duct having a second end communicating with the venturi tube opening.

25. (Currently Amended) The kitchen oven of claim 23 or 24, wherein said ducting includes a duct enclosure at least partially surrounding the venturi tube opening

and communicating with said second end of said transfer duct for receiving the positive air flow.

26. (Original) The kitchen oven of claim 25, wherein said duct enclosure has closed sides and top with an open bottom.

27. (Currently Amended) The kitchen oven of claim 23 or 24, wherein said first end of said transfer duct is mounted on a rear surface of said downwardly extending duct and an opening is provided between said transfer duct and said downwardly extending duct.

28. (Currently Amended) The kitchen oven of claim 23 or 24, wherein said second end of said transfer duct is spaced rearwardly from the oven back wall and includes an opening opposite the venturi tube opening for discharging the positive air flow toward the venturi tube opening, said free-flow opening being formed by the space between said oven back wall and said transfer duct.

29. (Original) The kitchen oven of claim 27, wherein said second end of said transfer duct is spaced rearwardly from the oven back wall and includes an opening opposite the venturi tube opening for discharging the positive air flow toward the venturi tube opening, said free-flow opening being formed by the space between said oven back wall and said transfer duct.